



L'huile des records du monde

## LUBE P - SAE 5W-30

Synthetic oil for Diesel and gasoline engines.

**LOW SAPS and FUEL ECONOMY**

### APPLICATIONS

Specifically developed to meet the **PSA B71 2290 standard of 'Peugeot Citroën Automobiles'**. Suitable for most\* of the PSA group vehicles for which a LOW SAPS oil reducing fuel consumption and polluting exhausts emissions is required. This oil is particularly recommended for vehicles fitted with particulate filters (FAP/DPF).

Meets the requirements of any other Diesel or gasoline engine recommending or allowing the use of a SAE 5W-30 oil meeting ACEA C2, ACEA A5/B5-07, API SN, API SM/CF or Fiat 9.55535-S1 specifications: Fiat, Toyota, ...

### MAIN PHYSICAL DATA

		Units	5W-30
Density at	20° C	kg/m <sup>3</sup>	850
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	59.4
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	10.1
Viscosity index			158
Flash point Cleveland open cup		° C	>200
Pour point		° C	- 45
Dynamic viscosity at	- 30° C	mPa.s	5500

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

**LOW SAPS** technology (lower levels of sulphated ashes, Sulphur and Phosphorous)

→ Extends particulate filters lifetime on Diesel engines

→ Optimizes the catalytic converters efficiency

Low level of HTHS at 150°C for a better reduction of fuel consumption

→ Optimizes environmental protection and polluting emissions reduction

Outstanding resistance to oxidation, even to EMHV (methyl ester from vegetable oils also called diester) and better protection against wear

→ Allows safe extended oil drain intervals

Tested according to engine tests and specific PSA laboratory tests

→ Use of a single oil for most\* vehicles of the PSA group

### APPROVALS

Peugeot Citroën Automobiles

PSA B71 2290 (2012 issue)

### SPECIFICATIONS

ACEA C2-10 ; ACEA A5/B5-07

API SN, API SM/CF

Fiat 9.55535-S1

\* In EW gasoline engines series until EURO IV, we recommend the use of a PSA B71 2296 approved lubricant (YACCO LUBE FR 5W-40 with PSA B71 2296 approval)

