DURON TM/MC XL 10W-40

000003000712

| 000003000712 | | |
|------------------------------------|---|--|
| Version 3.0 | Revision Date 2016/10/05 | Print Date 2016/10/05 |
| SECTION 1. IDENTIFICATION | | |
| Product name : | DURON TM/MC XL 10W-40 | |
| Product code : | DXL14P20, DXL14IBC, DXL14DRM, D DXL14C16, DXL14, DXL14BLK | DXL14DCT, |
| Manufacturer or supplier's details | Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2 Canada | |
| Emergency telephone num- ber | Suncor Energy: +1 403-296-3000; Canutec Transportation: 1-888- 226-88 996-6666; Poison Control Centre: Consult local te emergency number(s). | |
| Recommended use of the cher | nical and restrictions on use | |
| Recommended use : | DURON XL 10W40 is an engine oil for stroke compression and spark ignition ed ambient conditions. Mobile equipm heavy duty highway and off highway o smaller trucks and cars. This product many types of wet clutch transmission tems. | engines under extend- nent applications include perations, as well as may also be used in |

Prepared by

: Product Safety: +1 905-804-4752

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| Appearance | viscous liquid |
|------------|--------------------------|
| Colour | Light amber. |
| Odour | Mild petroleum oil like. |

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry

: Eye contact Ingestion Inhalation

DURON TM/MC XL 10W-40

000003000712



| Revision Date 2016/10/05 | Print Date 2016/10/05 |
|---|--|
| Skin contact | |
| : None known. | |
| | |
| No component of this product present a equal to 0.1% is identified as probable, human carcinogen by IARC. | |
| No component of this product present a equal to 0.1% is identified as a carcino gen by ACGIH. | |
| | Skin contact : None known. No component of this product present a equal to 0.1% is identified as probable, human carcinogen by IARC. No component of this product present a equal to 0.1% is identified as a carcino |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Substance / Mixture | : | Mixture |
|---------------------|---|---------|
|---------------------|---|---------|

Hazardous components

| Chemical name | CAS-No. | Concentration |
|---|-------------|---------------|
| lubricating oils (petroleum), C15-30, hydrotreat- ed neutral oil-based | 72623-86-0 | 50 - 70 % |
| White mineral oil (petroleum) | 8042-47-5 | 30 - 50 % |
| lubricating oils (petroleum), C20-50, hydrotreat- ed neutral oil-based, high viscosity | 72623-85-9 | 20 - 30 % |
| lubricating oils (petroleum), C20-50, hydrotreat- ed neutral oil-based | 72623-87-1 | 5 - 10 % |
| distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | 1 - 5 % |
| Zinc alkyldithiophosphate | 113706-15-3 | 1 - 5 % |

SECTION 4. FIRST AID MEASURES

| If inhaled | : Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice. |
|---|---|
| In case of skin contact | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. |
| In case of eye contact | : Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. |
| Internet: lubricants.petro-canada.ca/msds | Page: 2 / |
| Deter Orneda is a Ornega Engeneration | TM Trade grandle of Oursean Francisco Line days line |

DURON TM/MC XL 10W-40



000003000712

| Version 3.0 | Revision Date 2016/10/05 | Print Date 2016/10/05 |
|---|---|-----------------------|
| | Obtain medical attention. | |
| If swallowed | Rinse mouth with water. DO NOT induce vomiting unless d cian or poison control center. Never give anything by mouth to a Seek medical advice. | |
| Most important symptoms and effects, both acute and delayed | : First aider needs to protect himsel | f. |

SECTION 5. FIREFIGHTING MEASURES

| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. |
|---|--|
| Unsuitable extinguishing media | : No information available. |
| Specific hazards during fire- fighting | : Cool closed containers exposed to fire with water spray. |
| Hazardous combustion prod- ucts | : Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur compounds (H2S), sulphur oxides (SOx), phosphorus oxides (POx), zinc oxides (ZnOx), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete com- bustion. |
| Further information | : Prevent fire extinguishing water from contaminating surface water or the ground water system. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protec- tive equipment and emer- gency procedures | : | Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. |
|---|---|---|
| Environmental precautions | • | If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities. |

SECTION 7. HANDLING AND STORAGE

DURON TM/MC XL 10W-40



000003000712

| Version 3.0 | Revision Date 2016/10/05 | Print Date 2016/10/05 |
|-----------------------------|--|--|
| Advice on safe handling | For personal protection see section Smoking, eating and drinking show plication area. In case of insufficient ventilation, we equipment. Avoid contact with skin, eyes and Do not ingest. Keep away from heat and sources Keep container closed when not in | uld be prohibited in the ap- wear suitable respiratory clothing. s of ignition. |
| Conditions for safe storage | : Store in original container. Containers which are opened must kept upright to prevent leakage. Keep in a dry, cool and well-ventil Keep in properly labelled containe To maintain product quality, do no light. | ated place. ers. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters / Permissible concentration | Basis |
|--|------------|-------------------------------------|--|-----------|
| lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | 72623-86-0 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist) | 5 mg/m3 | CA QC OEL |
| | | STEV (Mist) | 10 mg/m3 | CA QC OEL |
| | | TWA (Inhal- able fraction) | 5 mg/m3 | ACGIH |
| White mineral oil (petroleum) | 8042-47-5 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist) | 5 mg/m3 | CA QC OEL |
| | | STEV (Mist) | 10 mg/m3 | CA QC OEL |
| | | TWA (Inhal- able fraction) | 5 mg/m3 | ACGIH |
| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity | 72623-85-9 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist) | 5 mg/m3 | CA QC OEL |
| | | STEV (Mist) | 10 mg/m3 | CA QC OEL |
| | | TWA (Inhal- able fraction) | 5 mg/m3 | ACGIH |
| lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | 72623-87-1 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business. $Page: 4 \ / \ 10$ Trademark of Suncor Energy Inc. Used under licence.

DURON TM/MC XL 10W-40



000003000712

| sion 3.0 | | Revision Date | e 2016/10/05 | Print Date | 2016/10/05 |
|-----------------------------|-----|---|--|---|---|
| | | | TWAEV (Mist) | 5 mg/m3 | CA QC OE |
| | | | STEV (Mist) | 10 mg/m3 | CA QC OE |
| | | | TWA (Inhal- able fraction) | 5 mg/m3 | ACGIH |
| Engineering measures | : | No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. | | | |
| Personal protective equipme | ent | | | | |
| Respiratory protection | 1 | ventilation is p that exposures Respirator sel exposure leve | rovided or expo s are within reco ection must be b | ess adequate local ex sure assessment der mmended exposure based on known or an of the product and the respirator. | monstrates guidelines. nticipated |
| Filter type | : (| organic vapou | r filter | | |
| Hand protection Material | : 1 | neoprene, nitri | ile, polyvinyl alc | ohol (PVA), Viton(R). | |
| Remarks | i | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. | | | |
| Eye protection | | Wear face-shi problems. | eld and protectiv | ve suit for abnormal p | processing |
| Skin and body protection | t | | ount of dangero | ation to its type, to the | |
| Protective measures | 1 | handling the p Wash contami | roduct. nated clothing b ewash station a | preaks and immediat before re-use. and safety shower are | - |
| Hygiene measures | i | ing the inside, | before re-use. | ted clothing and glov posed skin thoroughl | |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | : viscous liquid |
|------------|----------------------------|
| Colour | : Light amber. |
| Odour | : Mild petroleum oil like. |

DURON TM/MC XL 10W-40

000003000712



| rsion 3.0 | Revision Date 2016/10/05 | Print Date 2016/10/05 |
|--|--|--------------------------------|
| Odour Threshold | : No data available | |
| рН | : No data available | |
| Pour point | : -42 °C (-44 °F) | |
| Boiling point/boiling range | : No data available | |
| Flash point | : 229 °C (444 °F) Method: Cleveland open cup | |
| Fire Point | : 241 °C (466 °F) | |
| Auto-Ignition Temperature | : No data available | |
| Evaporation rate | : No data available | |
| Flammability | : Low fire hazard. This material r will occur. | nust be heated before ignition |
| Upper explosion limit | : No data available | |
| Lower explosion limit | : No data available | |
| Vapour pressure | : No data available | |
| Relative vapour density | : No data available | |
| Density | : 0.8619 kg/l (15 °C / 59 °F) | |
| Solubility(ies) | | |
| Water solubility | : insoluble | |
| Partition coefficient: n- octanol/water | : No data available | |
| Viscosity | | |
| Viscosity, kinematic | : 107.5 cSt (40 °C / 104 °F) | |
| | 15.52 cSt (100 °C / 212 °F) | |
| Explosive properties | : Do not pressurise, cut, weld, br pose containers to heat or sour | |

SECTION 10. STABILITY AND REACTIVITY

| Possibility of hazardous reac- | : Hazardous polymerisation does not occur. |
|---|---|
| tions | Stable under normal conditions. |
| Conditions to avoid | : No data available |
| Incompatible materials | : Reactive with oxidizing agents and water. |
| Hazardous decomposition | : May release COx, H2S, smoke and irritating vapours when |
| products | heated to decomposition. |
| Internet: lubricants.petro-canada.ca/msds | Page: 6 / 10 |
| Petro-Canada is a Suncor Energy business. | ™ Trademark of Suncor Energy Inc. Used under licence. |

DURON TM/MC XL 10W-40

SECTION 11. TOXICOLOGICAL INFORMATION

000003000712

Version 3.0



Print Date 2016/10/05

| Information on likely route Eye contact Ingestion Inhalation Skin contact | es of exposure |
|---|--|
| Acute toxicity | |
| Product: | |
| Acute oral toxicity | : Remarks: No data available |
| Acute inhalation toxicity | : Remarks: No data available |
| Acute dermal toxicity | : Assessment: The substance or mixture has no acute derr toxicity |
| Components: | |
| Iubricating oils (petroleum Acute oral toxicity | h), C15-30, hydrotreated neutral oil-based: : LD50 (Rat): > 5,000 mg/kg, |
| Acute inhalation toxicity | : LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist |
| Acute dermal toxicity | : LD50 (Rabbit): > 2,000 mg/kg, |
| White mineral oil (petroleu | ım): |
| Acute oral toxicity | : LD50 (Rat): > 5,000 mg/kg, |
| Acute inhalation toxicity | : LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist |
| Acute dermal toxicity | : LD50 (Rabbit): > 2,000 mg/kg, |
| Iubricating oils (petroleum Acute oral toxicity | n), C20-50, hydrotreated neutral oil-based, high viscosity: LD50 (Rat): > 5,000 mg/kg, |
| Acute inhalation toxicity | : LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist |
| Acute dermal toxicity | : LD50 (Rabbit): > 2,000 mg/kg, |
| Iubricating oils (petroleum Acute oral toxicity | h), C20-50, hydrotreated neutral oil-based: LD50 (Rat): > 5,000 mg/kg, |
| Acute inhalation toxicity | : LC50 (Rat): > 5.2 mg/l |
| et: lubricants.petro-canada.ca/msd | is P |

DURON TM/MC XL 10W-40



000003000712

| Exposure time: 4 h Test atmosphere: dust/mist : LD50 (Rabbit): > 2,000 mg/kg, rent-dewaxed heavy paraffinic: : LD50 (Rat): > 5,000 mg/kg, : LD50 (Rabbit): > 5,000 mg/kg, | |
|---|--|
| rent-dewaxed heavy paraffinic: : LD50 (Rat): > 5,000 mg/kg, | |
| : LD50 (Rat): > 5,000 mg/kg, | |
| : LD50 (Rabbit): > 5,000 mg/kg, | |
| | |
| | |
| | |
| | |
| itation | |
| | |
| | |
| sation | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| Toxicity to fish | : Remarks: No data available | |
|---|---------------------------------|--|
| Toxicity to daphnia and other aquatic invertebrates | : Remarks: No data available | |

DURON TM/MC XL 10W-40



000003000712

| Version 3.0 | Revision Date 2016/10/05 | Print Date 2016/10/05 |
|-------------------------------|------------------------------|-----------------------|
| Toxicity to algae | | |
| | Remarks: No data available | |
| Toxicity to bacteria | : Remarks: No data available | |
| | | |
| Persistence and degradability | | |
| Product: | | |
| Biodegradability | Remarks: No data available | |
| Bioaccumulative potential | | |
| No data available | | |
| Mobility in soil | | |
| No data available | | |
| Other adverse effects | | |
| No data available | | |

SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods | |
|---------------------|--|
| Waste from residues | The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal. |

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

DURON TM/MC XL 10W-40

000003000712

Version 3.0



Print Date 2016/10/05

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

| The components of this product are reported in the following inventories: | | |
|---|---|--|
| DSL | On the inventory, or in compliance with the inventory | |
| TSCA | All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption. | |
| ELINCS | At least one component is not listed in EINECS but all such components are listed in ELINCS. | |

SECTION 16. OTHER INFORMATION

| For Copy of SDS | : | Internet: lubricants.petro-canada.ca/msds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-804-4752 |
|-----------------|---|---|
| Prepared by | : | Product Safety: +1 905-804-4752 |
| Revision Date | : | 2016/10/05 |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.